

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Issued by DBI Certification A/S, notified body No. 2531.

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

Product group 1

Scope: Thermal insulation products

The product fulfils the essential characteristic of **reaction to fire**:

Class A1

Intended use: Thermal insulation products for building equipment and industrial installations

produced by or for

Skamol A/S
Sletvej 2C
DK-8310 Tranbjerg J

and produced in the manufacturing plant (s)

CPA10015

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 14306:2009 + A1:2013 : **Thermal insulation products for building equipment and industrial installations – Factory made calcium silicate (CS) products - Specification**

under system 1 for the performance set out in this certificate are applied and that the performance of the construction product is assessed to remain constant.

The attached annexes form part of this certificate.

Date of issue: **2019-07-17**.

This certificate will remain valid as long as neither the harmonized standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly unless suspended or withdrawn by the notified product certification body.

(This certificate supersedes the previous version of this certificate, issued 2019-03-20)

This certificate was first issued 2014-08-01.



Thomas Anthony Wilson
Responsible for evaluation



Dan Bluhme
Responsible for certification decision

The certificate shall be reproduced in extenso
– extracts only with written permission from DBI Certification A/S.

 **DANAK**

Prod. Reg. Nr. 7023

EXTENT

| Type | Description |
|---|--|
| SKAMOPRO 225, SKAMOPRO 300, SKAMOTEC 225, SkamoEnclosure Board, SkamoDoor Board 225, SkamoDoor Board 250, SkamoCovering 300, SkamoDoor Board 300. | Calcium silicate boards with density of 225 -300 kg/m ³ , maximum dimensions 2440 x 1220 mm, maximum thickness 100 mm |

TEST DOCUMENTATION

| Accredited Laboratory | Report no. | Date |
|-----------------------|------------|------------|
| DBI | PF13386 | 2010-09-22 |
| DBI | PC10253 | 2010-09-22 |
| DBI | PHA10687 | 2015-06-04 |

TECHNICAL BASIS

| Designation | Identification | Date |
|---------------------------|---|---------------------------|
| Specifications | S12.05uk SKAMOPRO225,250,300 S12.06uk SkamoEnclosure Board | Specifications |
| Supplementary information | R12090.xlsx | Supplementary information |

The certificate shall be reproduced in extenso
 – extracts only with written permission from DBI Certification A/S.